

UNMATCHED PRODUCTIVITY STARTS HERE.

The Hauler 800, now available with an ELiTE lithium powertrain activated by Samsung SDI battery technology or with a fuel-efficient 13.5 hp EFI gas engine, powers through your toughest workdays. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 vehicles have everything you need to finish job after job.



8.4 CU FT

CARGO BED

900LB

TOWING CAPACITY

800LB

VEHICLE LOAD CAPACITY

2 PASSENGER

SEATING

ZERO MAINTENANCE

ELITE LITHIUM BATTERY







ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights High/Low Beam
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger (ELiTE Only)
- Fuel/Oil Gauge (Gas Only)

CUSHMAN.COM

HAULER® 800

Welded Steel with E-Coat & E Injection Mo Forest G 110 in (279 49 in (12 47 in (119.4 cm) 69.5 in (176.5 cm) (v 65.5 in (16 37 in (94 cm) Front / 3 4.3 in (10. 8.4 cu ft (0	olded TPO Green 3.4 cm) 5 cm) (No Canopy) W/ Struts & Roof) 6.4 cm)
Injection Mo Forest G 110 in (279 49 in (12 47 in (119.4 cm) 69.5 in (176.5 cm) (v 65.5 in (16 37 in (94 cm) Front / 3 4.3 in (10	olded TPO Green 3.4 cm) 5 cm) (No Canopy) W/ Struts & Roof) 6.4 cm)
Forest G 110 in (278 49 in (12 47 in (119.4 cm) 69.5 in (176.5 cm) (v 65.5 in (16 37 in (94 cm) Front / 3 4.3 in (10	Green 3.4 cm) 5 cm) (No Canopy) N/ Struts & Roof) 6.4 cm) 8 in (96.5 cm) Rear
49 in (12 47 in (119.4 cm) 69.5 in (176.5 cm) (v 65.5 in (16 37 in (94 cm) Front / 3 4.3 in (10	5 cm) (No Canopy) N/ Struts & Roof) 6.4 cm) 8 in (96.5 cm) Rear
49 in (12 47 in (119.4 cm) 69.5 in (176.5 cm) (v 65.5 in (16 37 in (94 cm) Front / 3 4.3 in (10	5 cm) (No Canopy) N/ Struts & Roof) 6.4 cm) 8 in (96.5 cm) Rear
47 in (119.4 cm) 69.5 in (176.5 cm) (v 65.5 in (16 37 in (94 cm) Front / 3 4.3 in (10	(No Canopy) n/ Struts & Roof) 6.4 cm) 8 in (96.5 cm) Rear
69.5 in (176.5 cm) (v 65.5 in (16 37 in (94 cm) Front / 3 4.3 in (10.	w/ Struts & Roof) 6.4 cm) 8 in (96.5 cm) Rear
37 in (94 cm) Front / 3 4.3 in (10	8 in (96.5 cm) Rear
4.3 in (10.	
	.9 cm)
8.4 cu ft (0	
•••••••••••••••••••••••••••••••••••••••	.24 m3)
Roto-Molded P	olyethylene
56.7V Li-Ion Battery	4-Cycle, 24.5 ci (401cc
N/A	Single Cylinder OHV
11.7 HP (8.7 kW) Peak	13.5 hp (10.1 kW)
48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
2.2 Elite - Single Pack	One, 12V Maintenance Fr
Peda	al
N/A	Replaceable Industria Rated Dry Cartridge
N/A	Pressurized Oil Systen
N/A	Spin-On
N/A	Air Cooled
N/A	5.96 Gallon (22.6 L) tar
Motor Shaft Direct Drive	Continuously Variable Transmission
Differential w/ F	Helical Gears
Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse
16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)
2-Person (Bench)
753 lb (342 kg)	761 lb (345.2 kg)
800 lb (363 kg)	791 lb (359 kg)
800 lb (36	i2.9 kg)
400 lb (18	1.4 kg)
900 lb (40	18.2 kg)
18.9 ft (5	i.8 m)
16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)
ON	
	8.4 cu ft (0 28.5 in (L) x 44.5 in (72.4 cm x 113 cm Roto-Molded P 56.7V Li-Ion Battery N/A 11.7 HP (8.7 kW) Peak 48V Primary, 12V Auxiliary 2.2 Elite - Single Pack Peda N/A N/A N/A N/A N/A N/A N/A N/

STEERING	Self-Compensating Rack and Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	18 x 8.5 -8 (6 Ply Rated)

